








4010ST Flex Lances
APS #40-029 Parker Polyflex Hose - Black Jacket

| Part Number | Min. I.D. | Max. O.D. | Max. Working Pressure | Min. Burst Pressure | Min. Bend Radius | Weight |
|-------------|---|---|---|--|---|---|
| # |  |  |  |  |  |  |
| | In. / mm | In. / mm | PSI / Bar | PSI / Bar | In. / mm | Lbs./Ft. kg/m |
| 2440N-06V91 | 0.40" 10 mm | 0.77" 20 mm | 20,300 1400 | 50,750 3500 | 7.50" 191 mm | 0.47 0.70 |





Construction: Polyoxymethylene core tube, high strength wire reinforced and a polyamide outer cover.

Applications: Chemical resistant hose for hydraulic tools, pressure testing of offshore equipment and high pressure heat exchanger tube cleaning in petro chemical and power plants.

Fittings: See below.

Temperature Range: -40° F and +140° F (-40° C and +60° C). Contact Polyflex for temperatures outside this range.

Example: 40-029-4141-025 is a 4010ST 3/4"-16 Type M x 3/4"-16 Type M x 25 feet long

| End Fitting Code | Thread | Overall Length | Diam. R / Hex Size H | MAWP PSI/Bar | Illustration |
|------------------------------|-------------|-------------------------|-------------------------|----------------|---|
| Type M (F) Swivel 41 | 3/4"-16 | A 2.95"/75 mm | H 1.00"/25 mm | 21,750 1500 |  |
| MP (M) Tube Nipples 27 | 9/16"-18 LH | A 3.80"/97 mm | H 1.22"/31 mm | 20,000 1379 |  |