







4113ST Flex Lances
APS #40-015 Parker Polyflex Hose - Gray Jacket

Part Number	Min. I.D.	Max. O.D.	Max. Working Pressure	Min. Burst Pressure	Min. Bend Radius	Weight	
#							
	In. / mm	In. / mm	PSI / Bar	PSI / Bar	In. / mm	Lbs./Ft.	kg/m
2440N-08V37	0.50" 13 mm	0.88" 22 mm	20,400 1407	51,000 3517	7.87" 200 mm	0.63	0.94

Construction: Polyamide core tube, high strength wire reinforced and a polyamide outer cover.



Applications: Flexible, lightweight, chemical resistant alternative to steel pipe and rubber hose for applications such as waterblasting, gas transfer, chemical injection, wireline logging services, and pressure testing.

Fittings: See below.

Example: 40-015-1212-025 is a 4113ST 1/2" NPT (M) x 1/2" NPT (M) x 25 feet long



Temperature Range: -40° F and +140° F (-40° C and +60° C). Contact Polyflex for temperatures outside this range.

End Fitting Code	Thread	Overall Length	Diam. R / Hex Size H	MAWP PSI/Bar	Illustration
NPT (M) 12	1/2" NPT	A 3.75"/95 mm	H 1.13"/29 mm	15,000 1034	
Type M (F) Swivel 43	1"-12	A 3.53"/90 mm	H 1.25"/32 mm	20,400 1407	
MP (M) Tube Nipple 27 29	9/16"-18 LH 3/4"-16 LH	A 4.20"/107 mm 4.13"/105 mm	R 1.13"/29 mm 1.13"/29 mm	20,000 1379	