








**6005ST Flex Lances**  
**APS #40-022 Parker Polyflex Hose - Blue Jacket**

Part Number	Min. I.D.	Max. O.D.	Max. Working Pressure	Min. Burst Pressure	Min. Bend Radius	Weight	
#							
	In. / mm	In. / mm	PSI / Bar	PSI / Bar	In. / mm	Lbs./Ft.	kg/m
2640D-03V32	0.20" 5 mm	0.51" 13 mm	36,230 2499	90,580 6247	6.88" 175 mm	0.27	0.40

**Construction:** Polyoxymethylene core tube, high strength wire reinforced and a polyamide outer cover.



**Applications:** High pressure waterblast cleaning of heat exchanger tubes in petrochemical and power plants. Especially suitable for hydraulic pre-tensioning equipment, specialized pressure fitted sleeve and coupling removal equipment. Pressure testing, operations of portable jacks and remote pressure sensing devices.



**Temperature Range:** -40° F and +140° F (-40° C and +60° C). Contact Polyflex for temperatures outside this range.

**Fittings:** See below.

**Example:** 40-022-3939-025 is a 6005ST 9/16"-18 Type M x 9/16"-18 Type M x 25 feet long

End Fitting Code	Thread	Overall Length	Diam. R / Hex Size H	MAWP PSI/Bar	Illustration
Type M (F) Swivel 39	9/16"-18	<b>A</b> 3.07"/78 mm	<b>H</b> 0.75"/19 mm	36,230 2499	
HP (M) Tube Nipple 25 27	3/8"-24 LH 9/16"-18 LH	<b>A</b> 4.06"/103 mm 4.42"/112 mm	<b>R</b> 0.75"/19 mm 0.75"/19 mm	36,230 2499	
HP (F) Swivel Fitting 46	9/16"-18	<b>A</b> 3.07"/78 mm	<b>H</b> 0.75"/19 mm	36,230 2499	