







6013ST Flex Lances
APS #40-019 Parker Polyflex Hose - Blue Jacket

Part Number	Min. I.D.	Max. O.D.	Max. Working Pressure	Min. Burst Pressure	Min. Bend Radius	Weight
#						
	In. / mm	In. / mm	PSI / Bar	PSI / Bar	In. / mm	Lbs./Ft. kg/m
2640N-08V32	0.50" 13 mm	0.97" 25 mm	26,090 1799	65,220 4498	11.41" 290 mm	0.91 1.36




Construction: Polyamide core tube, high strength wire reinforced and a polyamide outer cover.

Applications: Flexible, chemical resistant alternative to steel pipe delivery hose in waterblasting, hydrodemolition systems, chemical injection and gas transfer, oil field wireline logging services, and pressure testing.

Temperature Range: -40° F and +140° F (-40° C and +60° C). Contact Polyflex for temperatures outside this range.

Fittings: See below.

Example: 40-019-4343-025 is a 6013ST 1"-12 Type M x 1"-12 Type M x 25 feet long

End Fitting Code	Thread	Overall Length	Diam. R / Hex Size H	MAWP PSI/Bar	Illustration
Type M (F) Swivel 43	1"-12	A 4.25"/108 mm	H 1.25"/32 mm	26,090 1799	
MP (M) Tube Nipple 27 29	9/16"-18 LH 3/4"-16 LH	A 4.30"/109 mm 4.20"/107 mm	R 1.25"/32 mm 1.25"/32 mm	20,000 1379	