







6020ST Flex Lances
APS #40-017 Parker Polyflex Hose - Blue Jacket


Part Number	Min. I.D.	Max. O.D.	Max. Working Pressure	Min. Burst Pressure	Min. Bend Radius	Weight	
#							
	In. / mm	In. / mm	PSI / Bar	PSI / Bar	In. / mm	Lbs./Ft.	kg/m
2640N-12V32	0.75" 19 mm	1.30" 33 mm	20,290 1399	50,720 3498	13.77" 350 mm	1.41	2.10

Construction: Polyamide core tube, high strength wire reinforced and a polyamide outer cover.

Applications: Flexible, chemical resistant alternative to steel pipe for waterblasting, hydrodemolition, gas transfer, oil field snubbing, hydraulic workover systems and chemical injection service.


Fittings: See below.

Example: 40-017-4545-025 is a 6020ST 1-5/16" Type M x 1-5/16" Type M x 25 feet long



Temperature Range:

-40° F and +140° F (-40° C and +60° C). Contact Polyflex for temperatures outside this range.

End Fitting Code	Thread	Overall Length	Diam. R / Hex Size H	MAWP PSI/Bar	Illustration
Type M (F) Swivel 45	1-5/16"-12	A 4.26"/108 mm	H 1.50"/38 mm	20,290 1399	
MP (M) Tube Nipple 30	1"-14 LH	A 5.48"/139 mm	R 1.69"/43 mm	20,000 1379	