







6108ST Flex Lances
APS #40-021 Parker Polyflex Hose - Blue Jacket

Part Number	Min. I.D.	Max. O.D.	Max. Working Pressure	Min. Burst Pressure	Min. Bend Radius	Weight	
#							
	In. / mm	In. / mm	PSI / Bar	PSI / Bar	In. / mm	Lbs./Ft.	kg/m
2740D-05V32	0.32" 8 mm	0.67" 17 mm	36,230 2499	90,580 6247	7.87" 200 mm	0.47	0.70




Construction: Polyoxymethylene core tube, high strength wire reinforced and a polyamide outer cover.

Applications: Pressure testing and ultra high pressure waterblast delivery hose for industrial cleaning and shipbuilding industries for coatings removal and water jet cutting equipment.

Fittings: See below.

Temperature Range: -40° F and +140° F (-40° C and +60° C). Contact Polyflex for temperatures outside this range.

Example: 40-021-4141-025 is a 6108ST 3/4"-16 Type M x 3/4"-16 Type M x 25 feet long

End Fitting Code	Thread	Overall Length	Diam. R / Hex Size H	MAWP PSI/Bar	Illustration
Type M (F) Swivel 41 42	3/4"-16 7/8"-14	A 2.97"/75 mm 3.47"/88 mm	H 1.00"/25 mm 1.25"/32 mm	36,230 2499	
HP (M) Tube Nipple 28	9/16"-18 LH	A 4.15"/105 mm	R 1.00"/25 mm	36,230 2499	